

**AD 2 AERODROMES****FASH AD 2.1 AERODROME LOCATION INDICATOR AND NAME****FASH - STELLENBOSCH (1265)****FASH AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA**

1	ARP Coordinates and site at AD	Ref. Point: S335850 E0184922
2	Direction and distance from city	3.5NM SW of Stellenbosch
3	Elevation / Reference temperature	Elev: 321 FT / 15°C
5	MAG VAR / Annual change	23°W/1.3 Westwards
6	AD Operator, address, telephone, telefax, e-mail, AFS address and, if available, website address	Authority Supervising the Aerodrome and Remarks: PRIV AD CHF: Stellenbosch Flying Club P O Box 12653, DIE BOORD 7613 TEL: (021) 880-1907 or (021) 880-0294 FAX: (021) 880-1264
7	Types of traffic permitted (IFR/VFR)	VFR

FASH AD 2.3 OPERATIONAL HOURS

1	AD Operator	MON - FRI: 0700 - 1500
8	Fuelling	Supplier : SHELL./ Stellenbosch Flying Club. TEL : (021) 880-1907 or (021) 880-0294. HOD : MON - SUN : 0600 - 1600.

FASH AD 2.4 HANDLING SERVICES AND FACILITIES

2	Fuel/oil types	AVGAS/ OIL : 100LL Aeroshell, ASO W100.
3	Fuelling facilities/Capacity	20 000 Litres

FASH AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD Category for fire fighting	Category 2
2	Rescue Equipment	Fire tender 2 200 litres medium pumper
3	Capability for removal of disabled aircraft	Yes

FASH AD 2.8 Aprons, Taxiways and Check Locations Data

1	Apron Surface and Strength	LCN 20
2	Taxiway width, surface and Strength	LCN 10

FASH AD 2.10 AERODROME OBSTACLES

Poles 4 m high from GND erected 150 m from FNA of RWY 01.

FASH AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE & MAG BRG	Dimensions of RWY (M)	Strength (PCN) and surface of RWY and SWY	THR coordinates	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
01 19		760 x 16	ASPH LCN 20		
Designations RWY NR	Slope of RWY-SWY	SWY dimensions (M)	CWY dimensions (M)	Strip dimensions (M)	OFZ
1	7	8	9	10	11
01 19					
Remarks 12					
- ACFT must adhere to the RWYs, TWYs and park in the parking area.					

FASH AD 2.14 APPROACH AND RUNWAY LIGHTING

Remarks:
Runway not for general public use, for club member use and training.

FASH AD 2.20 LOCAL TRAFFIC REGULATIONS

Only club members will be permitted to operate Helicopters at aerodrome, provided that such Helicopters are permanently based at aerodrome and that members have agreed to specific standard operating procedures in writing.



FASH AD 2.22 FLIGHT PROCEDURES

| RHC RWY 19 and Left Hand Circuit for RWY 01 apply and to be flown west of/and 2.5NM FASH.

| ACFT joining overhead the airfield shall join at 1 800 FT ALT or below: descend on dead side for 1300FT ALT downwind and remain clear of the FACT CTR/TMA unless under FACT control.

Departing aircraft shall only commence the crosswind turn at 1000 FT ALT or above, provided that terrain clearance criteria are not violated.

Operation of constant speed units shall be in accordance with noise abatement procedures as stipulated in the relevant standard operating procedures. (See AIC 20.12)

| Airfield data available on Frequency 119.3 MHz and airfield limited to VFR operations only.

FASH AD 2.23 ADDITIONAL INFORMATION

Increased bird activity on and around AD.