

RNAV (GNSS) INSTRUMENT APPROACH CHART FOR FABL RWY 20

Serial Number	Path Descriptor	Waypoint Identifier	LATITUDE	LONGITUDE	Flyover	Fix	Course °M(°T)	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KT IAS)	VPA/TCH	Magnetic Variation (°W)	Navigation Specification
10	IF	UNLOD	28°55'05.3500"S	026°25'03.3600"E	N	IAF	292 (270)	-	-	+8000	-	-	22	RNP APCH
20	TF	BL2T1	28°55'05.5200"S	026°18'13.1400"E	N	IF	292 (270)	6.00	-	+6500	230	-	22	RNP APCH
10	IF	IMGUR	28°49'04.6000"S	026°18'15.6900"E	N	IAF	-	-	-	+8000	-	-	22	RNP APCH
20	TF	BL2T1	28°55'05.5200"S	026°18'13.1400"E	N	IF	202 (180.5)	6.00	-	+6500	230	-	22	RNP APCH
10	IF	DUGSO	28°55'03.4600"S	026°11'22.9200"E	N	IAF	-	-	-	+8000	-	-	22	RNP APCH
20	TF	BL2T1	28°55'05.5200"S	026°18'13.1400"E	N	IF	112 (090.3)	6.00	-	+6500	230	-	22	RNP APCH
10	IF	BL2T1	28°55'05.5200"S	026°18'13.1400"E	N	IF	-	-	-	+6000	-	-	22	RNP APCH
20	TF	BL2F1	29°00'06.2900"S	026°18'11.0100"E	N	FAF	202 (180.5)	5.00	-	+6000	230	-3.00°/50'	22	RNP APCH
30	TF	BL2MP	29°04'55.0400"S	026°18'08.9700"E	Y	MAPT	203 (180.5)	-	-	-	-	-	22	RNP APCH
10	IF	BL2MP	29°04'55.0400"S	026°18'08.9700"E	Y	MAPT	203 (180.5)	4.80	-	@4471	-	-	22	RNP APCH
20	VA	-	-	-	N	MATF	203 (180.5)	11.70	-	+6500	-	-	22	RNP APCH
30	DF	UNLOD	28°55'05.3500"S	026°25'03.3600"E	N	-	-	37.25	-	+8000	-230	-	22	RNP APCH
40	HM	UNLOD	28°55'05.3500"S	026°25'03.3600"E	Y	MAHF	292 (270)	-	R	+8000	-230	-	22	RNP APCH

RNAV HOLDING

FACILITY	INBOUND TRACK	MAX/MIN FL	FACILITY
UNLOD 28°55'05.3500"S 026°25'03.3600"E	292°M/270°T	FL100 FL080	Right hand racecourse pattern. 1 MIN MAX

