

RNAV (GNSS) INSTRUMENT APPROACH CHART FOR FACT RWY 01

Serial Number	Path Descriptor	Waypoint Identifier	LATITUDE	LONGITUDE	Flyover	Fix	Course *M(*T)	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KT IAS)	VPA/TCH	Magnetic Variation (*W)	Navigation Specification
10	IF	EKBEV	34°11'59.7600"S	018°31'58.0700"E	-	IAF	-	-	-	+6100	250	-	25.28	RNP APCH
20	TF	CT1T1	34°10'13.7600"S	018°40'01.0800"E	-	IF	100 (075.17)	6.91	-	+3700	-	-	25.28	RNP APCH
10	IF	IBGEL	34°16'55.0700"S	018°42'09.0700"E	-	IAF	-	-	-	+6100	250	-	25.28	RNP APCH
20	TF	CT1T1	34°10'13.7600"S	018°40'01.0800"E	-	IF	010 (345.17)	6.91	-	+3700	-	-	25.28	RNP APCH
10	IF	UTIRO	34°08'27.2400"S	018°48'03.7500"E	-	IAF	-	-	-	+6500	250	-	25.28	RNP APCH
20	TF	CT1T1	34°10'13.7600"S	018°40'01.0800"E	-	IF	280 (255.17)	6.91	-	+3700	-	-	25.28	RNP APCH
10	IF	CT1T1	34°10'13.7600"S	018°40'01.0800"E	-	IF	-	-	-	+3700	-	-	25.28	RNP APCH
20	TF	CT1F1	34°04'08.8600"S	018°38'05.0100"E	-	FAF	010 (345.17)	6.28	-	1800	-	3.0°/-	25.28	RNP APCH
30	TF	CT1SD	34°01'46.9583"S	018°37'19.9213"E	-	SDF	010 (345.17)	2.40	-	-	-	-	25.28	RNP APCH
40	TF	RW01	33°59'15.8600"S	018°36'32.0100"E	Y	MAPT	010 (345.17)	2.60	-	+194.39	-	3.0°/50'	25.28	RNP APCH
50	FA	RW01	33°59'15.8600"S	018°36'32.0100"E	-	-	-	-	-	-	-	-	25.28	RNP APCH
60	DF	CT1M1	33°55'46.6505"S	018°35'25.6863"E	-	MATF	010 (345.17)	3.00	-	-	-	-	25.28	RNP APCH
70	TF	RIV	33°47'58.4500"S	018°21'52.1000"E	-	-	329 (304.41)	12.74	-	-	-	-	25.28	RNP APCH
80	TF	CT1M2	33°58'13.1100"S	018°18'16.1200"E	-	MATF	-	-	-	+6100	-	-	25.28	RNP APCH
90	TF	EKBEV	34°11'59.7600"S	018°31'58.0700"E	-	-	166 (140.3)	17.90	-	+6100	-	-	25.28	RNP APCH
100	HM	EKBEV	34°11'59.7600"S	018°31'58.0700"E	Y	MAHF	-	-	R	+6100	250	-	25.28	RNP APCH

RNAV HOLDING

FACILITY	INBOUND TRACK	MAX/MIN FL	FACILITY
EKBEV 34°11'59.7600"S 018°31'58.0700"E	100°M/075.17°T	<u>FL080</u> <u>6100</u>	Right hand racecourse pattern. 1 MIN Outbound leg. MAX 250KT IAS

