

INSTRUMENT APPROACH CHART FOR FAGG RWY 29

Serial Number	Path Descriptor	Waypoint Identifier	LATITUDE	LONGITUDE	Flyover	FIX	Course °M(°T)	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KT IAS)	VPA/TCH	Magnetic Variation (°W)	Navigation Specification
10	IF	IMPEG	33°59'36.197"S	022°44'38.555"E	-	IAF	-	-	-	+6500	-210	-	26.91	RNP APCH
20	TF	ETLAG	33°59'53.431"S	022°36'13.777"E	-	IF	294 (267.6)	7	-	3900	-	-	26.91	RNP APCH
10	IF	TILAS	34°06'53.888"S	022°36'34.164"E	-	IAF	-	-	-	5800	-210	-	26.91	RNP APCH
20	TF	ETLAG	33°59'53.431"S	022°36'13.777"E	-	IF	024 (357.7)	7	-	3900	-	-	26.91	RNP APCH
10	IF	ETLAG	33°59'53.431"S	022°36'13.777"E	-	-	-	-	-	3900	210	-	26.91	RNP APCH
20	TF	GG2F1	34°00'05.390"S	022°30'13.172"E	-	FAF	294 (267.7)	5	-	2500	-	-	26.91	RNP APCH
30	TF	RW29	34°00'18.683"S	022°23'21.568"E	Y	MAPT	294 (267.7)	5.7	-	@698	185	2.94°/50	26.91	RNP APCH
40	FA	RW29	34°00'18.683"S	022°23'21.568"E	-	-	-	-	-	-	-	-	26.91	RNP APCH
50	DF	GG2M1	34°00'38.138"S	022°12'56.253"E	-	MATF	294 (267.8)	8.7	-	-	-	-	26.91	RNP APCH
60	TF	GG2M2	34°11'03.955"S	022°13'23.770"E	-	MATF	204 (177.9)	10.4	-	-	-	-	26.91	RNP APCH
70	TF	TILAS	34°06'53.888"S	022°36'34.164"E	-	MATF	104 (077.9)	19.7	-	5800	-	-	26.91	RNP APCH
80	HM	TILAS	34°06'53.888"S	022°36'34.164"E	Y	MAHF	024 (357.7)	-	R	4600	-230	-	26.91	RNP APCH

RNAV HOLDING

FACILITY	INBOUND TRACK	MAX/MIN FL	FACILITY
TILAS 34°06'53.888"S 022°36'34.164"E	024°M/357.7°T	8000 4600	Right hand racecourse pattern. 1 MIN Outbound leg. MAX 230KT IAS