

AERODROME/
HELIPORT
CHART - ICAO

25°23'29.70"S
031°05'57.40"E

ELEV 2829'
GUND 52.0'

KRUGER APP: 119.20
TWR: 119.20
LOWVELD: 129.40

KRUGER
MPUMALANGA INTL
FAKN

ELEV, ALT & HGT IN FEET
DIST IN METERS
BRG ARE MAG

F0060/26NOTAMN
Q) FAJA/QOAXX/IV/BO/A/000/999/2523S03106E005
A) FAKN B) 2603251331 C) PERM
E) HAND AMEND FAKN AD-01 CHART DATED 31 DEC 2020 AS FLW:
RWY 05 CWY DIMENSIONS TO READ 220.
RWY 23 CWY DIMENSIONS TO READ 223.
RWY 05/23 TODA (M) DIMENSIONS TO READ 3320.

VAR 19°N 2020
ANNUAL RATE
OF CHANGE 0.6°W

GENERAL AVIATION

TERMINAL

CONTROL TOWER

PAPI 3°

3200 x 45m ASPHALT

KRUGER
MPUMALANGA
NDB 405.0
PK
25°23'00.80"S
031°06'32.10"E

KRUGER
MPUMALANGA
FAKN ARP
25°23'29.70"S
031°05'57.40"E
2829'

DTHR 500m

ELEV 2825'

CWY 60m x 150m

RESA 300m x 90m

SCALE: 1:23 000
0 100 200 300 Meters

RWY LIGHTING					
RWY	ALS	PAPI	RTHL	REDL	RENL
05	HALS-1	3°L	GREEN	WHITE	RED
23	SALS	3°L	GREEN	WHITE	RED

OTHER: WDI, APN Flood lights, TWY Lights

PHYSICAL CHARACTERISTICS

RWY	DIRECTION (T)	THR COORDINATES	THR ELEVATION	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	DTHR (m)	RESA (m)	CWY (m)	SLOPE	SURFACE	BEARING STRENGTH
05	034°	25°23'29.75"S 031°05'57.36"E	2825'	3100	3260	3100	2600	500	300	60	0.0003U	ASPH	PCN
23	214°	25°22'19.76"S 031°06'49.68"E	2828'	3097	3260	3097	2937	160	300	60	0.0003D	ASPH	56/F/B/X/T

EFF: 31 DEC 20

SOUTH AFRICAN



CIVIL AVIATION AUTHORITY

AD-01