

CHANGE: Maintenance (Waypoints: OR364, OR365, OR366),
Hold direction, ARP Elevation).

RNAV (GNSS) STANDARD ARRIVAL CHART FROM AVAGO TO FAOR RWY 21L													
Serial Number	Path Descriptor	Waypoint Identifier	LATITUDE	LONGITUDE	Flyover	Turn Direction	Course °M(°T)	Distance (NM)	Altitude (FT)	Speed (KT IAS)	VPA/TCH	Magnetic Variation (°W)	Navigation Specification
10	IF	AVAGO	25°43'09.9000" S	027°26'39.3600" E	Y	-	-	-	+FL110	250	-	19.91	RNAV 1
20	TF	OR364	25°53'42.5153" S	027°45'30.5957" E	-	-	141 (121.8)	20.00	+FL110	250	-	19.91	RNAV 1
30	TF	OR365	26°04'07.7200" S	028°04'16.2600" E	-	-	141 (121.6)	19.84	+8000	250	-	19.91	RNAV 1
40	TF	OR366	25°57'20.1900" S	028°06'21.0200" E	-	-	035 (051.5)	7.03	+8000	210	-	19.91	RNAV 1
50	FM	-	-	-	-	-	035 (051.5)	-	+8000	210	-	19.91	RNAV 1

RNAV (GNSS) STANDARD ARRIVAL CHART FROM AVAGO TO FAOR RWY 21L (Communication Failure Squawk 7600)													
Serial Number	Path Descriptor	Waypoint Identifier	LATITUDE	LONGITUDE	Flyover	Turn Direction	Course °M(°T)	Distance (NM)	Altitude (FT)	Speed (KT IAS)	VPA/TCH	Magnetic Variation (°W)	Navigation Specification
10	IF	AVAGO	25°43'09.9000" S	027°26'39.3600" E	Y	-	-	-	+FL110	250	-	19.91	RNAV 1
20	TF	OR364	25°53'42.5153" S	027°45'30.5957" E	-	-	141 (121.8)	20.00	+FL110	250	-	19.91	RNAV 1
30	TF	OR365	26°04'07.7200" S	028°04'16.2600" E	-	-	141 (121.6)	19.84	+8000	250	-	19.91	RNAV 1
40	TF	OR366	25°57'20.1900" S	028°06'21.0200" E	-	-	035 (051.5)	7.03	+8000	210	-	19.91	RNAV 1
50	TF	UVLOG	25°53'18.6400" S	028°11'19.6100" E	-	-	068 (048.2)	6.02	+8000	210	-	19.91	RNAV 1

*RNAV 1 REQUIRED

RNAV HOLDING			
FACILITY	INBOUND TRACK	MIN/MAX FL	TYPE
AVAGO 25°43'09.9000" S 027°26'39.3600" E	141°M/321°M (121.8°T / 301.8°T)	FL280 FL110	Right hand racecourse pattern. 1 Minute 30 seconds, MAX 250KT IAS.

