

ILS INSTRUMENT APPROACH TO FAPE RWY 26

Fix/Waypoint Identifier	LATITUDE	LONGITUDE	Fix	Course °M	Distance (NM)	Altitude (FT)	Magnetic Variation (°W)	Navigation Specification
10.1 DME/PEV	-	-	-	-	-	+2500	29.79	VOR/DME REQUIRED
5.4 DME/PDI	33°56'18.3914"S	025°42'24.7179"E	FAP	268	-	+1900	29.79	VOR/DME REQUIRED
LTP/FTP	33°59'03.9306"S	025°57'05.5769"E	RWY26	268	5.21	+241	29.79	VOR/DME REQUIRED
PEV	33°59'33.0079"S	025°36'20.7533"E	VOR/DME	-	-	-	29.79	VOR/DME REQUIRED
LOC PDI	33°59'42.8759"S	025°35'50.3798"E	LOC	-	-	-	29.79	VOR/DME REQUIRED
GP PDI	33°59'12.0376"S	025°36'58.7779"E	GP	-	-	-	29.79	VOR/DME REQUIRED
DME PDI	33°59'12.0057"S	025°36'58.8040"E	DME	-	-	-	29.79	VOR/DME REQUIRED
-	-	-	-	R268	-	+2000	29.79	VOR/DME REQUIRED

ILS HOLDING

FACILITY	INBOUND/OUTBOUND TRACK	MAX/MIN FL	TYPE
PEV VOR/DME 33°59'33.0079" S 025°36'20.7533" E	R088/088°M	FL070 <u>3000'</u>	Left-hand racecourse pattern. 1 min OUBD. MAX 230KT IAS

CHANGE: Procedure Maintenance