

AERODROME/ HELIPORT CHART - ICAO 24°57'40.76"S 031°35'19.77"E **ELEV 1040'** **GUND 45'**

SKUKUZA TIBA: 124.80
LOWVELD INFO: 119.00
APRON: 125.25

SKUKUZA FASZ

ELEV, ALT & HGT IN FEET
DIST IN METERS
BRG ARE MAG

CAUTION

1. Pilots to exercise caution during take-off and landing due to high concentration of birds.
2. Wildlife may be present if the fencing is breached.



NOTE

1. CONTACT SKUKUZA ON FREQ 125.5 MHZ AT LEAST 10MIN PRIOR ARRIVAL WITH ETA.
2. USE FREQ 119.00: OUTSIDE 10NM
USE FREQ 124.80: WITHIN 10NM

24°57'10"S
24°57'20"S
24°57'30"S
24°57'40"S
24°57'50"S
24°58'S



ANNUAL RATE OF CHANGE 0°7' W



RWY LIGHTING					
RWY	ALS	PAPI	RTHL	REDL	RENL
17	NIL	NIL	NIL	NIL	NIL
35	NIL	NIL	NIL	NIL	NIL

OTHER: NIL

31°34'50"E 31°35'E 31°35'10"E 31°35'20"E 31°35'30"E 31°35'40"E 31°35'E

PHYSICAL CHARACTERISTICS

RWY	DIRECTION (T)	THR COORDINATES	THR ELEVATION	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	SWY (m)	CWY (m)	SLOPE	SURFACE	BEARING STRENGTH	CIRCUIT
17	156°	24°57'19.09"S 031°35'08.98"E	1034'	1550	1822	1672	1550	122	272	0.008D	ASPH	PCN 25/F/B/X/T	R/H
35	336°	24°58'02.42"S 031°35'30.57"E	992'	1550	1703	1550	1550	NIL	153	0.008U	ASPH		L/H

CHANGE: LOWVELD (LASS) Frequency/VAR

SCALE: 1:13 500
0 100 200 300 Meters