

CHANGE: New Procedure

RNAV (GNSS) ARRIVAL CHART FROM UNPOM TO FAOR RWY 03R													
Serial Number	Path Descriptor	Waypoint Identifier	LATITUDE	LONGITUDE	Flyover	Turn Direction	Course °M(°T)	Distance (NM)	Altitude (FT)	Speed (KT IAS)	VPA/TCH	Magnetic Variation (°W)	Navigation Specification
10	IF	UNPOM	26°41'48.1900" S	028°52'02.8600" E	Y	-	-	-	+FL110	250	-	19.91	RNAV 1
20	TF	OR391	26°37'06.3582" S	028°38'08.9185" E	-	-	311 (290.6)	13.30	+FL110	250	-	19.91	RNAV 1
30	TF	OR392	26°30'55.3400" S	028°19'58.8700" E	-	-	311 (290.7)	17.42	8000	250	-	19.91	RNAV 1
40	TF	ETLIG	26°41'48.0000" S	028°16'59.0000" E	-	L	214 (193.9)	11.17	+8000	210	-	19.91	RNAV 1

*RNAV 1 REQUIRED

RNAV HOLDING			
FACILITY	INBOUND/OUTBOUND TRACK	MIN/MAX FL	TYPE
UNPOM 25°41'48.1900" S 028°52'02.8600 E	311°M /131°M (290.6°T) / (110.6°T)	FL280 FL110	Right hand racecourse pattern. 1 Minute 30 seconds OUBD. MAX 250KT IAS.