

CHANGE: New Procedure

RNAV (GNSS) ARRIVAL CHART FROM OKPIT TO FAOR RWY 21L													
Serial Number	Path Descriptor	Waypoint Identifier	LATITUDE	LONGITUDE	Flyover	Turn Direction	Course °M(°T)	Distance (NM)	Altitude (FT)	Speed (KT IAS)	VPA/TCH	Magnetic Variation (°W)	Navigation Specification
10	IF	OKPIT	25°27'44.2200" S	028°44'32.5600" E	-	-	-	-	+FL110	250	-	19.91	RNAV 1
20	TF	OR383	25°53'00.9283" S	028°46'28.1844" E	-	-	195 (176.1)	25.26	+FL110	250	-	19.91	RNAV 1
30	TF	OR384	25°59'03.5992" S	028°42'07.5523" E	-	R	233 (213.0)	7.19	9000	250	-	19.91	RNAV 1
40	TF	OR385	26°03'46.6471" S	028°29'18.3599" E	-	R	268 (247.8)	12.47	+8000	210	-	19.91	RNAV 1
50	FM	-	-	-	-	R	036 (016.0)	-	+8000	210	-	19.91	RNAV 1

RNAV (GNSS) ARRIVAL CHART FROM OKPIT TO FAOR RWY 21L (Communication Failure Squawk 7600)													
Serial Number	Path Descriptor	Waypoint Identifier	LATITUDE	LONGITUDE	Flyover	Turn Direction	Course °M(°T)	Distance (NM)	Altitude (FT)	Speed (KT IAS)	VPA/TCH	Magnetic Variation (°W)	Navigation Specification
10	IF	OKPIT	25°27'44.2200" S	028°44'32.5600" E	-	-	-	-	+FL110	250	-	19.91	RNAV 1
20	TF	OR383	25°53'00.9283" S	028°46'28.1844" E	-	-	195 (176.1)	25.26	+FL110	250	-	19.91	RNAV 1
30	TF	OR384	25°59'03.5992" S	028°42'07.5523" E	-	R	233 (213.0)	7.19	9000	250	-	19.91	RNAV 1
40	TF	OR385	26°03'46.6471" S	028°29'18.3599" E	-	R	268 (247.8)	12.47	+8000	210	-	19.91	RNAV 1
50	TF	ETGAV	25°57'22.7800" S	028°27'26.2700" E	-	R	036 (016.0)	6.60	+8000	210	-	19.91	RNAV 1

*RNAV 1 REQUIRED

OKPIT RNAV HOLDING			
FACILITY	INBOUND TRACK	MIN/MAX FL	TYPE
OKPIT 25°27'44.2200" S 028°44'32.5600" E	(195° M / 015° M) (356.1° T / 176.1° T)	FL280 FL110	Left hand racecourse pattern. 1 Minute 30 Seconds OUBD. MAX 250KT IAS.