

CHANGE: Maintenance (Waypoints: OR370, OR371, OR372, OR373 & Hold direction).

RNAV (GNSS) ARRIVAL CHART FROM AVAGO TO FAOR RWY 03R													
Serial Number	Path Descriptor	Waypoint Identifier	LATITUDE	LONGITUDE	Flyover	Turn Direction	Course °M(°T)	Distance (NM)	Altitude (FT)	Speed (KT IAS)	VPA/TCH	Magnetic Variation (°W)	Navigation Specification
10	IF	AVAGO	25°43'09.9000" S	027°26'39.3600" E	Y	-	-	-	+FL110	250	-	19.91	RNAV 1
20	TF	OR370	25°53'42.3733" S	027°45'30.3471" E	-	-	141 (121.8)	20.00	+FL110	250	-	19.91	RNAV 1
30	TF	OR371	26°04'46.2400" S	028°05'25.8800" E	-	-	141 (121.6)	21.07	9000	250	-	19.91	RNAV 1
40	TF	OR372	26°08'34.8800" S	028°05'55.7900" E	-	R	193 (173.3)	3.83	9000	210	-	19.91	RNAV 1
50	TF	OR373	26°23'02.9400" S	028°00'04.8200" E	-	R	220 (200.0)	15.35	+8000	210	-	19.91	RNAV 1
60	FM	-	-	-	-	-	220 (200.0)	-	+8000	210	-	19.91	RNAV 1

RNAV (GNSS) ARRIVAL CHART FROM AVAGO TO FAOR RWY 03R (Communication Failure Squawk 7600)													
Serial Number	Path Descriptor	Waypoint Identifier	LATITUDE	LONGITUDE	Flyover	Turn Direction	Course °M(°T)	Distance (NM)	Altitude (FT)	Speed (KT IAS)	VPA/TCH	Magnetic Variation (°W)	Navigation Specification
10	IF	AVAGO	25°43'09.9000" S	027°26'39.3600" E	Y	-	-	-	+FL110	250	-	19.91	RNAV 1
20	TF	OR370	25°53'42.3733" S	027°45'30.3471" E	-	-	141 (121.8)	20.00	+FL110	250	-	19.91	RNAV 1
30	TF	OR371	26°04'46.2400" S	028°05'25.8800" E	-	-	141 (121.6)	21.07	9000	250	-	19.91	RNAV 1
40	TF	OR372	26°08'34.8800" S	028°05'55.7900" E	-	R	193 (173.3)	3.83	9000	210	-	19.91	RNAV 1
50	TF	OR373	26°23'02.9400" S	028°00'04.8200" E	-	R	220 (200.0)	15.35	+8000	210	-	19.91	RNAV 1
60	TF	VEKOP	26°36'45.8000" S	027°54'30.9200" E	-	-	220 (200.0)	14.56	+8000	210	-	19.91	RNAV 1

*RNAV 1 REQUIRED

AVAGO RNAV HOLDING			
FACILITY	INBOUND TRACK	MIN/MAX FL	TYPE
AVAGO 25°43'09.9000" S 027°26'39.3600" E	141°M / 321°M (121.8°T / 301.8°T)	FL280 FL110	Left hand racecourse pattern. 1 Minute 30 seconds OUBD. MAX 250KT IAS.