

CHANGE: ARP ELEV, WPT Name (OR386, OR387, OR388)

RNAV (GNSS) ARRIVAL CHART FROM NIBEX TO FAOR RWY 21L													
Serial Number	Path Descriptor	Waypoint Identifier	LATITUDE	LONGITUDE	Flyover	Turn Direction	Course °M(°T)	Distance (NM)	Altitude (FT)	Speed (KT IAS)	VPA/TCH	Magnetic Variation (°W)	Navigation Specification
10	IF	NIBEX	26°49'25.5600" S	027°40'13.4100" E	-	-	-	-	+FL110	250	-	19.91	RNAV 1
20	TF	OR386	26°32'41.1735" S	027°54'21.7451" E	-	-	058 (037.2)	20.95	+FL110	250	-	19.91	RNAV 1
30	TF	OR387	26°21'40.9700" S	028°03'36.4800" E	-	-	057 (037.1)	13.76	+8000	210	-	19.91	RNAV 1
40	TF	OR388	26°07'04.4034" S	028°07'35.4391" E	-	L	034 (013.8)	15.00	+8000	210	-	19.91	RNAV 1
50	TF	UVLOG	25°53'18.6400" S	028°11'19.6100" E	-	-	034 (013.8)	14.13	+8000	210	-	19.91	RNAV 1

*RNAV 1 REQUIRED

RNAV HOLDING			
FACILITY	INBOUND/OUTBOUND TRACK	MIN/MAX FL	TYPE
NIBEX 26°49'25.5600"S 027°40'13.4100"E	058° M / 238° M (037.2°T / 217.2° T)	FL280 <u>FL110</u>	Right hand racecourse pattern. 1 Minute 30 Seconds OUBD. MAX 250KT IAS.

