

CHANGE: New Procedure

RNAV (GNSS) ARRIVAL FROM OKPIT TO FAOR RWY 03R													
Serial Number	Path Descriptor	Waypoint Identifier	LATITUDE	LONGITUDE	Flyover	Turn Direction	Course °M(°T)	Distance (NM)	Altitude (FT)	Speed (KT IAS)	VPA/TCH	Magnetic Variation (°W)	Navigation Specification
10	IF	OKPIT	25°27'44.2200" S	028°44'32.5600" E	-	-	-	-	+FL110	250	-	19.91	RNAV 1
20	TF	OR393	25°36'01.4387" S	028°38'25.7026" E	-	-	233 (213.8)	9.94	FL110	250	-	19.91	RNAV 1
30	TF	OR394	25°45'38.9545" S	028°31'18.2938" E	-	-	233 (213.8)	11.55	+FL110	250	-	19.91	RNAV 1
40	TF	OR395	26°09'23.3481" S	028°25'16.9463" E	-	L	212 (192.9)	24.28	8000	250	-	19.91	RNAV 1
50	TF	OR396	26°20'08.4709" S	028°22'32.4593" E	-	-	213 (192.9)	11.00	+8000	210	-	19.91	RNAV 1
60	FM	-	-	-	-	-	213 (192.9)	-	+8000	210	-	19.91	RNAV 1

*RNAV 1 REQUIRED

RNAV (GNSS) ARRIVAL FROM OKPIT TO FAOR RWY 03R (Communication Failure)													
Serial Number	Path Descriptor	Waypoint Identifier	LATITUDE	LONGITUDE	Flyover	Turn Direction	Course °M(°T)	Distance (NM)	Altitude (FT)	Speed (KT IAS)	VPA/TCH	Magnetic Variation (°W)	Navigation Specification
10	IF	OKPIT	25°27'44.2200" S	028°44'32.5600" E	-	-	-	-	+FL110	250	-	19.91	RNAV 1
20	TF	OR393	25°36'01.4387" S	028°38'25.7026" E	-	-	233 (213.8)	9.94	FL110	250	-	19.91	RNAV 1
30	TF	OR394	25°45'38.9545" S	028°31'18.2938" E	-	-	233 (213.8)	11.55	+FL110	250	-	19.91	RNAV 1
40	TF	OR395	26°09'23.3481" S	028°25'16.9463" E	-	L	212 (192.9)	24.28	8000	250	-	19.91	RNAV 1
50	TF	OR396	26°20'08.4709" S	028°22'32.4593" E	-	-	213 (193.9)	11.00	+8000	210	-	19.91	RNAV 1
60	TF	ETLIG	26°41'48.0000" S	028°16'59.0000" E	-	-	213 (193.0)	22.16	+8000	210	-	19.91	RNAV 1

RNAV HOLDING			
FACILITY	INBOUND/OUTBOUND TRACK	MAX/MIN FL	FACILITY
OKPIT 25°27'44.2200"S 028°44'32.5600"E	233°M (053°T)/ 213.8°M (033.8°T)	FL280 FL110	Right hand racecourse pattern. 1 Minute 30 Seconds OUBD. MAX 250KT IAS.