

CHANGE: New Procedure

RNAV (GNSS) ARRIVAL FROM UNPOM TO FAOR RWY 21L													
Serial Number	Path Descriptor	Waypoint Identifier	LATITUDE	LONGITUDE	Flyover	Turn Direction	Course °M(°T)	Distance (NM)	Altitude (FT)	Speed (KT IAS)	VPA/TCH	Magnetic Variation (°W)	Navigation Specification
10	IF	UNPOM	26°41'48.1900" S	028°52'02.8600" E	-	-	-	-	+FL110	250	-	19.91	RNAV 1
20	TF	OR368	26°33'14.8709" S	028°41'54.0439" E	-	-	334 (313.1)	12.47	+FL110	250	-	19.91	RNAV 1
30	TF	OR369	26°18'42.2500" S	028°24'44.5000" E	-	-	334 (313.2)	21.15	+8000	250	-	19.91	RNAV 1
40	TF	ETGAV	25°57'22.7800" S	028°27'26.2700" E	-	R	027 (006.5)	21.40	+8000	210	-	19.91	RNAV 1

*RNAV 1 REQUIRED

UNPOM RNAV HOLDING			
FACILITY	INBOUND TRACK	MIN/MAX FL	TYPE
UNPOM 26°41'48.1900" S 028°52'02.8600" E	334°M (313.1°T) / 154°M (134.1°T)	FL280 <u>FL110</u>	Right hand racecourse pattern. 1 Minute 30 seconds OUBD. MAX 250KT IAS.

