

CHANGE: Procedure Maintenance.

EFF: 29 OCT 26

AIR TRAFFIC & NAVIGATION SERVICES

RNP-01A

RNP INSTRUMENT APPROACH CHART FOR FAGY RWY 24															
Serial Number	Path Descriptor	Waypoint Identifier	LATITUDE	LONGITUDE	Flyover	Fix	Course °M(°T)	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KT IAS)	VPA/TCH	Magnetic Variation (°W)	Navigation Specification	
10	IF	ETMUP	29°02'47.8400" S	030°47'21.9500" E	-	IAF	-	-	-	FL080	-200	-	25.61	RNP APCH	
20	TF	GY2T1	28°59'28.8900" S	030°43'05.3200" E	-	IF	337(311.4)	5.00	L	+6300	-200	-	25.61	RNP APCH	
10	IF	IBLUX	28°55'43.3400" S	030°46'51.5400" E	-	IAF	-	-	-	7500	-200	-	25.61	RNP APCH	
20	TF	GY2T1	28°59'28.8900" S	030°43'05.3200" E	-	IF	247(221.4)	5.00	-	+6300	-200	-	25.61	RNP APCH	
10	IF	UDGOM	28°56'09.8100" S	030°38'48.9500" E	-	IAF	-	-	-	7500	-200	-	25.61	RNP APCH	
20	TF	GY2T1	28°59'28.8900" S	030°43'05.3200" E	-	IF	157(131.5)	5.00	R	+6300	-200	-	25.61	RNP APCH	
10	IF	GY2T1	28°59'28.8900" S	030°43'05.3200" E	-	IF	-	-	-	+6300	-	-	25.61	RNP APCH	
20	TF	GY2F1	29°03'14.3500" S	030°39'18.8100" E	-	FAF	247(221.4)	5.00	-	+5100	-	-	25.61	RNP APCH	
30	TF	RW24	29°06'59.6847" S	030°35'32.0378" E	Y	LPT/FTP	247(221.5)	5.00	-	@3522	-	3.0°/50'	25.61	RNP APCH	
10	CA	-	-	-	-	-	247(221.5)	-	-	+4500	-200	-	25.61	RNP APCH	
20	DF	ETMUP	29°02'47.8400" S	030°47'21.9500" E	-	-	-	-	L	@7000	-200	-	25.61	RNP APCH	
30	HM	ETMUP	29°02'47.8400" S	030°47'21.9500" E	-	MAHF	337(311.4)	-	L	+7000	-200	-	25.61	RNP APCH	

RNP HOLDING			
FACILITY	INBOUND/OUTBOUND TRACK	MAX/MNM FL	TYPE
ETMUP 29°02'47.8400" S 030°47'21.9500" E	337°M (311.4°T) / 157°M (131.5°T)	<u>FL110</u> <u>7000'</u>	Left-hand racecourse pattern. 1 MIN OUBD MAX 200KT IAS